	\$	~ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
FORM PTO-1390 (REV 10-94)	US DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFF	DOCKET #: 3397-112PU
TRANSMITTAL LE	ETTER TO THE UNITED STATES	
DESIGNATED/ELECTED OFI	FICE (DO/EO/US) CONCERNING A FIL	ING
UNI	DER 35 U.S.C. 371	
		U.S. APPLICATION NO.
		# 07.0.0.2.9.9.9.9
INTERNATIONAL APPLICATION NO	INTERNATIONAL FILING DATE	PRIORITY DATE CLAIMED
PCT/FI00/00746	September 01, 2000	September 01, 1999
TITLE OF INVENTION	artain Coater and Method for Curtain Coa	<b>4</b> 0
	urtain Coater and Method for Curtain Coa	iting
APPLICANT(S) FOR DO/EO/US		
	Timo KIIHA; Jukka KOSKINEN	
Applicant herewith submits to the Un	nited States Designated/Elected Office (DO/F	EO/IIS) the following items and other
information:	Emiles Benghated/Elected Office (DO)	20,03) the following items and other
198 de 19		
[x] This is a <b>FIRST</b> submission of	f items concerning a filing under 35 U.S.C. 3	71.
This is a <b>SECOND</b> or <b>SUBSE</b>	QUENT submission of items concerning a fi	Tingunder 35 U.S.C. 371
18t \ AVamination until the avarenties	national examination procedures (35 U.S.C. 3	71(f)) at any time rather than delay
39(1).	n of the applicable time limit set in 35 U.S.C.	371(b) and PCT Articles 22 and
4. [x]A proper Demand for International Column Science Priority date.	onal Preliminary Examination was made by t	the 19th month from the earliest
claimed priority date.		
a [x] is transmitted herewith (reg	plication as filed (35 U.S.C. 371(c)(2)) uired only if not transmitted by the Internatio	1.0
[x] A copy of the International Application as [x] is transmitted herewith (required bs. [x] has been transmitted by the c. [] is not required as the application of the complete control of the control	International Rureau	onal Bureau).
c. [] is not required, as the applic	antion was filed in the II + 1 C++ D · · ·	g Office (RO/US)
6 [] A translation of the International	al Application into English (35 U.S.C. 371(c)	(2)
[11]2 tillesterrients to the claims of the	ne international Application under PCT Artic	de 19 (35 U.S.C. 371(c)(3))
Opinion)	quired only if not transmitted by the Internati	onal Bureau). (See Reply to Written
b.[] have been transmitted by the	e International Bureau.	
c. [] have not been made; however	er, the time limit for making such amendmen	ts has NOT expired.
d.[] have not been made and will	Il not be made.	
9. [x] An oath or declaration of the in	ts to the claims under PCT Article 19 (35 U.S	.C. 371(c)(3)).
10 [] A translation of the annexes to t	the International Preliminary Examination Re	eport under PCT Article 36 (35
U.S.C. 371(c)(5)).	,	port and 1 of Thurse 50 (55
Items 11 to 16 Relow concern other	er document(s) or information included:	
11 [x]An Information Disclosure Stat	tement under 37 CFR 1 97 and 1 98	
12 [x] An assignment document for re	ecording. A separate cover sheet in compliance	ce with 37 CFR 3.28 and 3.31 is
included.		
13.[x]A FIRST preliminary amendments	ent.	
[] A SECOND or SUBSEQUI 14.[] A substitute specification.	ENI preliminary amendment.	
15.[] A change of power of attorney a	and/or address letter.	
16.[x]Other items or information (spe	ecify): PCT Publication Sheet, Int'l Prelimina	ry Examination Report, Reply to
Written Opinion, PCT Request,	PCT Demand, and Notification of the Record	ding of a Change.

JC19 Rac'd PUT/PTO M2 7 FEB 20280US

	U.S. APPLICATION NO (If known seed) C/ POS 696 62 INTERNATIONAL APPLICATION NO PCT/F100/00746			ATTORNEY'S DOCKET NUMBER 3397-112PUS			
17.	[x]The following fees	are submitted:					
No interest No int	ic National Fee (37 CFR) ch Report has been preparational preliminary examinternational preliminary einternational search fee pather international search fee (3 mational preliminary examall claims satisfied provisi	red by the EPO or JPO mination fee paid to USPT examination fee paid to US ad to USPTO (37 CFR 1.4 ary examination fee (37 C 7 CFR 1.445(a)(2)) paid t mination fee paid to USPT	CO (37 CFR 1.482) SPTO (37 CFR 1.482) 445(a)(2)) CFR 1.482) o USPTO CO (37 CFR 1.482)	\$	\$710.00 \$740.00 \$1040.00		
		ENTER APP	ROPRIATE BASIC FI	EE AMOU	UNT =	\$	890
Sur from	charge of \$130.00 for the earliest claimed p	furnishing the oath or or oriority date (37 CFR	declaration later that 1.492(e)).	n [] 20 []	30 months	\$	
	Claims	Number Filed	Number Extra	Ra	ite		
144	Total Claims	38 - 20 =	18	x <b>\$1</b>	8.00	\$	324
	idependent Claims	2 - 3 =		x <b>\$8</b>	4.00	\$	
[44 [47]	Multiple depe	ndent claim(s) (if appl	icable)	+ \$28	30.00	\$	
		то	OTAL OF ABOVE CAI	CULATI	ons =	\$	1214
Red	uction of ½ for filing b	by small entity, if appl	icable.			\$	
ि है। हैंड				SUBTO	TAL =	\$	1214
mor	essing fee of \$130.00 ths from the earliest cl	for furnishing the Englaimed priority date (3	lish translation later 7 CFR 1.492(f)).	than [] 2	20 [] 30 +	\$	
14 <sub>00</sub>			TOTAL NA	ATIONAL	FEE =	\$	1214
Fee acco	for recording the enclo mpanied by the appro	osed assignment (37 C priate cover sheet (37 c	FR 1.21(h)). The as CFR 3.28, 3.31). \$4	signmen	t must be property +	\$	40
:					TOTAL FEES	ENCLOSED	\$1254
					Amount to b	e refunded:	\$
	charged				charged:	\$	
b. [ c. [	E: Where an approp	posit Account No. <u>03-24</u> sed. hereby authorized to cheposit Account No. <u>03-2</u>	412 in the amount of parge any additional and 2412. A duplicate color of the color	\$ to fees whice opy of thi 195 has n	o cover the about the may be requised sheet is enclosed to the met.	ired, or credit	any
<u>Mich</u> Cohe 551 I	ALL CORRESPONDENG ael C. Stuart n, Pontani, Lieberman Fifth Avenue, Suite 121 York, New York 1017	& Pavane	Registra	C. Stuar tion Num 2) 687-27	nber: 35,698 F		0002

New York, New York 10176
Form PTO-1390 (REV 10-94)

page 2 of 2

10/069662 JC19 Rec'd PCT/PTO 27 FEB 2002

By Express Mail # EV072606280US · February 27, 2002

#### Attorney Docket # 3397-112PUS

#### IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re National Phase PCT Application of

Timo KIIHA et al.

International Appln. No.:

PCT/FI00/00746

International Filing Date:

September 01, 2000

For:

Curtain Coater and Method for Curtain Coating

#### PRELIMINARY AMENDMENT

Assistant Commissioner for Patents Washington, D.C. 20231

**BOX PCT** 

SIR:

Prior to examination of the above-identified application, amend the application as follows:

### IN THE SPECIFICATION (As amended by the Response to the Written Opinion):

Page 1 (Amended Sheet), before line 3, the paragraph beginning with "The present invention", insert the following title:

#### --FIELD OF THE INVENTION--.

Page 1 (Amended Sheet), delete lines 4 to 6 and insert therefor, the following new paragraph:

-- The present invention relates to a curtain coater and to a curtain-coating method.--

Page 1 (Amended Sheet), before line 8, the paragraph beginning with "In a curtain coater,", insert the following title:

#### --BACKGROUND OF THE INVENTION--.

Page 2, before line 20, the paragraph beginning with "It is an object", insert the following title:

#### --SUMMARY OF THE INVENTION--.

Page 3 (Amended Sheet), delete lines 17 to 23.

Page 4, before line 5, the paragraph beginning with "In the following,", insert the following paragraph and title:

-- Other objects and features of the present invention will become apparent from the following detailed description considered in conjunction with the accompanying drawings. It is to be understood, however, that the drawings are intended solely for purposes of illustration and not as a definition of the limits of the invention, for which reference should be made to the appended claims.

#### BRIEF DESCRIPTION OF THE DRAWINGS--.

Page 4, before line 16, the paragraph beginning with "Referring to FIG. 1,", insert the following title:

#### --DETAILED DESCRIPTION OF THE PRESENTLY PREFERRED EMBODIMENTS--.

Page 7, after the last line, insert the following paragraph:

--Thus, while there have been shown and described and pointed out fundamental novel features of the present invention as applied to a preferred embodiment thereof, it will be understood that various omissions and substitutions and changes in the form and details of the devices described and illustrated, and in their operation, and of the methods described may be made by those skilled in the art without departing from the spirit of the present invention. For example, it is expressly

intended that all combinations of those elements and/or method steps which perform substantially the same function in substantially the same way to achieve the same results are within the scope of the invention. Substitutions of elements from one described embodiment to another are also fully intended and contemplated. It is also to be understood that the drawings are not necessarily drawn to scale but that they are merely conceptual in nature. It is the intention, therefore, to be limited only as indicated by the scope of the claims appended hereto.—.

Page 8 (Amended Sheet), line 1, delete "Claims:" and insert therefor --What is claimed is:--.

#### IN THE CLAIMS:

Cancel claims 1 to 12, without prejudice.

Add the following new claims:

13. A curtain coater for coating a moving web of paper or board, the curtain coater comprising:

an applicator nozzle positioned above the web to be coated and configured so as to apply coating mix ejected therefrom to a surface of the web in a continuous curtain extending uniformly over a cross-machine width of the web; and

a doctoring means configured to remove a boundary air layer traveling on the surface of the web to be coated and being located upstream in the travel direction of the web of an impingement point of the coating mix curtain on the surface of the web and being located on the same side of the web as the applicator nozzle, the surface of the doctoring means facing the web being curved to support the web.

- 14. The curtain coater of claim 13, further comprising a gas-injection nozzle located downstream in the travel direction of the web of the applicator nozzle, configured so as to extend over the cross-machine width of the web, and adapted to blow gas toward the coating mix curtain applied to the web from the applicator nozzle.
- 15. The curtain coater of claim 13, further comprising a suction nozzle extending over the cross-machine width of the web and adapted to said doctoring means so as to remove by suction the boundary air layer traveling on the surface of the web.
- 16. The curtain coater of claim 14, further comprising a suction nozzle extending over the cross-machine width of the web and adapted to said doctoring means so as to remove by suction the boundary air layer traveling on the surface of the web.
- 17. The curtain coater of claim 15, wherein an inlet opening of the suction nozzle is on a downstream-directed wall of the doctoring means.
- 18. The curtain coater of claim 15, wherein an inlet opening of the suction nozzle is on a downstream-directed wall of the doctoring means.
- 19. The curtain coater of claim 15, wherein an inlet opening of the suction nozzle is on a surface of the doctoring means facing the web.
- 20. The curtain coater of claim 16, wherein an inlet opening of the suction nozzle is on a surface of the doctoring means facing the web.
- 21. The curtain coater of claim 13, wherein a distance between the web and the curved surface of the doctoring means is up to  $500 \,\mu$  m.

- 22. The curtain coater of claim 14, wherein a distance between the web and the curved surface of the doctoring means is up to  $500 \,\mu$  m.
- 23. The curtain coater of claim 15, wherein a distance between the web and the curved surface of the doctoring means is up to  $500 \mu m$ .
- 24. The curtain coater of claim 16, wherein a distance between the web and the curved surface of the doctoring means is up to  $500 \mu m$ .
- 25. The curtain coater of claim 17, wherein a distance between the web and the curved surface of the doctoring means is up to  $500 \,\mu$  m.
- 26. The curtain coater of claim 18, wherein a distance between the web and the curved surface of the doctoring means is up to  $500 \,\mu$  m.
- 27. The curtain coater of claim 19, wherein a distance between the web and the curved surface of the doctoring means is up to  $500 \,\mu$ m.
- 28. The curtain coater of claim 20, wherein a distance between the web and the curved surface of the doctoring means is up to  $500 \mu m$ .
  - 29. The curtain coater of claim 13, wherein said doctoring means is a doctor bar.
  - 30. The curtain coater of claim 14, wherein said doctoring means is a doctor bar.
  - 31. The curtain coater of claim 15, wherein said doctoring means is a doctor bar.

- 32. The curtain coater of claim 16, wherein said doctoring means is a doctor bar.
- 33. The curtain coater of claim 21, wherein said doctoring means is a doctor bar.
- 34. The curtain coater of claim 22, wherein said doctoring means is a doctor bar.
- 35. The curtain coater of claim 23, wherein said doctoring means is a doctor bar.
- 36. The curtain coater of claim 24, wherein said doctoring means is a doctor bar.
- 37. The curtain coater of claim 13, wherein that a distance along the surface of the web from a downstream end of said doctoring means to the impingement point under said applicator nozzle is less than 50 mm.
- 38. The curtain coater of claim 14, wherein that a distance along the surface of the web from a downstream end of said doctoring means to the impingement point under said applicator nozzle is less than 50 mm.
- 39. The curtain coater of claim 15, wherein that a distance along the surface of the web from a downstream end of said doctoring means to the impingement point under said applicator nozzle is less than 50 mm.
- 40. The curtain coater of claim 16, wherein that a distance along the surface of the web from a downstream end of said doctoring means to the impingement point under said applicator nozzle is less than 50 mm.

- 41. The curtain coater of claim 17, wherein that a distance along the surface of the web from a downstream end of said doctoring means to the impingement point under said applicator nozzle is less than 50 mm.
- 42. The curtain coater of claim 18, wherein that a distance along the surface of the web from a downstream end of said doctoring means to the impingement point under said applicator nozzle is less than 50 mm.
- 43. The curtain coater of claim 19, wherein that a distance along the surface of the web from a downstream end of said doctoring means to the impingement point under said applicator nozzle is less than 50 mm.
- 44. The curtain coater of claim 20, wherein that a distance along the surface of the web from a downstream end of said doctoring means to the impingement point under said applicator nozzle is less than 50 mm.
- 45. The curtain coater of claim 21, wherein that a distance along the surface of the web from a downstream end of said doctoring means to the impingement point under said applicator nozzle is less than 50 mm.
- 46. The curtain coater of claim 29, wherein that a distance along the surface of the web from a downstream end of said doctoring means to the impingement point under said applicator nozzle is less than 50 mm.
- 47. A curtain-coating method for coating a moving web of paper or board, comprising:

passing the web to be coated to a coater station; and

using an applicator nozzle positioned above the web to apply coating mix ejected therefrom to a surface of the web as a continuous curtain extending uniformly over a cross-machine width of the web;

removing a boundary air layer traveling along with the web from the surface of the web facing the applicator nozzle with a doctoring means located upstream in the travel direction of the web of the applicator nozzle; and

supporting the web with a curved surface of the doctoring means.

- 48. The curtain-coating method of claim 47, further comprising blowing gas toward the coating mix curtain being applied from the applicator nozzle from a gas-injection nozzle located downstream of the applicator nozzle in the travel direction of the web, the gas-injection nozzle extending over the cross-machine width of the web.
- 49. The curtain-coating method of claim 47, wherein the boundary air layer traveling on the surface of the web is removed by suction from a suction nozzle adapted to said doctoring means.
- 50. The curtain-coating method of claim 48, wherein the boundary air layer traveling on the surface of the web is removed by suction from a suction nozzle adapted to said doctoring means.

#### **REMARKS**

This preliminary amendment is presented to place the application in proper form for examination and to eliminate multiple dependency from the present claims. No new matter has been added. Early examination and favorable consideration of the above-identified application is earnestly solicited.

Any additional fees or charges required at this time in connection with the application may be charged to our Patent and Trademark Office Deposit Account No. 03-2412.

Respectfully submitted, COHEN, PONTANI, LIEBERMAN & PAVANE

By:

Michael C. Stuart Reg. No. 35,698

551 Fifth Avenue, Suite 1210

New York, N.Y. 10176

(212) 687-2770

27 February 2002

1

#### Curtain coater and method for curtain coating

The present invention relates to curtain coater according to the preamble of claim 1 and to curtain-coating method according to the preamble of claim 10.

In a curtain coater, the coating mix is applied to the surface of a moving web of paper or board, generally from a nozzle extending over the full cross-machine width of the web and located above the web being coated, whereby the coating mix can fall onto the web surface as curtain-like shower. Curtain coating is categorized as a noncontacting coating method, wherein the applicator itself makes no contact with the web being coated, but instead, the coating mix is applied to the web surface in the form of a free-falling curtain of coating mix. The technique of curtain coating is described, e.g., in publication DE 196 22 080.

20

25

30

15

10

During its travel, a moving web gathers a thin boundary layer of air that moves along with the web. In curtain coaters, the momentum of the coating mix applied to the web surface is small as compared to the momentum of the coating mix amount directed from a jet applicator, for instance, which means that the boundary air layer traveling on the web surface can easily scatter the curtain of coating mix flowing from the nozzle of a curtain coater thus making the applied coating layer uneven. With higher web speeds in the coater station, the problem is accentuated due to the faster speed of the boundary air layer and its higher momentum. Hence, the control of the

The state of the s

THE STATE CHARLE STATE STATE STATE STATE CHARLES STATE CHARLES STATE STA

the stand there is not the stand of the stan

25

30

boundary air layer behavior at higher web speeds becomes one of the most significant factors affecting the runnability of a curtain coater.

- The problem associated with the boundary air layer can be 5 diminished by way of, e.g., making the height of the falling curtain of coating mix larger thereby increasing its falling velocity or by increasing the amount of coating being applied, whereby the momentum of the coating mix curtain is increased and the falling curtain can more 10 readily penetrate through the boundary air layer traveling on the web surface. However, it is generally not possible to make the falling height of the coating mix curtain sufficiently large bacause the coating mix curtain begins to converge and separate into streamlets with a larger falling height. Moreover, the increase of the amount of the applied coating mix necessitates doctoring away the excess coating from the web surface.
- It is an object of the present invention to provide an entirely novel type of curtain coater and curtain-coating method offering an essential improvement in the reduction of the amount of boundary air penetration to the application zone of a curtain coater.

The goal of the invention is attained by way of placing a doctoring means upstream in front of the application point in the travel direction of the web being coated, the device serving to remove the boundary air layer from the surface of the traveling web. The purpose of the doctoring means is to bring about a significant reduction in the amount of the entrained air traveling along with

the web to the application zone. In one embodiment of the invention, the amount of the boundary air coming to the application zone is reduced by means of a suction nozzle cooperating with the air-doctoring element, whereby the boundary air layer is removed via the suction nozzle by a vacuum. Additionally, the adherence of the coating mix curtain to the web surface can be augmented by means of a gas-injection nozzle mounted downstream after the applicator nozzle in the travel direction of the web, whereby a gas jet can be directed from the gas-injection nozzle toward the coating mix curtain. Hereby, the combined momentum of the coating mix curtain and the gas jet becomes sufficiently energetic to force the coating mix to penetrate through the boundary air layer traveling on the web surface.

More specifically, the curtain coaters according to the invention are characterized by what is stated in the characterizing part of claims 1.

20

30

10

Furthermore, the curtain-coating method according to the invention is characterized by what is stated in the characterizing part of claims 10.

25 The invention offers significant benefits.

In a curtain coater according to the invention, the amount of boundary air traveling on the web being coated to the application zone can be reduced significantly as compared with conventional curtain coaters, whereby the coat quality and web runnability in the coater are improved. The web speed in a curtain coater according to

And the state of t

10

25

30

the invention can be readily increased because the boundary air layer can be removed effectively from the surface of the running web prior to application.

In the following, the invention will be examined in greater detail by making reference to the appended drawings in which

FIG. 1 shows schematically a cross-sectional side view of a conventional curtain coater; and

FIGS. 2-7 show schematically cross-sectional side views of different embodiments of curtain coaters according to the invention.

Referring to FIG. 1, the conventional curtain coater shown therein comprises an applicator nozzle 1 placed above a web 2 and extending in the cross-machine direction above the web 2 so as to permit application of the coating mix therefrom to the surface of the moving web 2. The travel direction of the web 2 is designated by an arrow. The boundary air layer traveling on the surface of the moving web 2 tends to deflect the curtain of coating mix being applied from the nozzle 1 in the travel direction of the moving web 2. At a sufficiently high travel speed of the web, the steady flow of the coating mix curtain is disturbed and a portion of the applied coating mix is blown along with the boundary air in the travel direction of the web 1, whereby certain areas on the surface of the web 2 may remain entirely uncoated.

In FIG. 2 is shown an embodiment of a curtain coater,

The state of the s

5

10

15

20

25

30

wherein there is located upstream in front of the application zoned formed its applicator nozzle 1, upstream in the travel direction of the web 2, a doctoring means 3 having a curved contour and extending over the crossmachine width of the web 2 so as to scatter the boundary air layer traveling on the surface of moving web 2 before the air layer can reach the application zone and cause there problems in the coat quality. The doctoring means 3 is disposed so that its curved contour is above the surface of the web 2. Generally, between the moving web 2 and the doctoring means 3 is formed a boundary air layer, the thickness of which is determined, among other factors, by the speed of the web 2 and the radius of curvature on the curved contour of the doctoring means. Typically, the thickness of the air layer remaining between the web 2 and the curved contour of the doctoring means 3 is in the range of 0-500 µm. The end point of the curved contour of the doctoring means 3 facing the web 2 is advantageously placed as close as possible to the starting point of the application zone under the nozzle 1, since a new layer of boundary air will be rapidly regenerated over a free length of the web downstream from the doctoring means 3. In practice, the boundary air layer can reach its original thickness within 50 mm of web travel.

In contrast to the arrangement of FIG. 2, the embodiment shown in FIG. 3 has the doctoring means 3 complemented with a suction channel 4 extending over the cross-machine width of the web 2 and having its inlet opening 7 located at the rear part of the doctoring means 3. In this fashion, the boundary air layer traveling on the surface

5

10

And the state of t

25

30

of the moving web 2 can be sucked into the suction channel 4.

In FIG. 4 is shown an arrangement wherein the inlet opening 7 of the suction channel 4 is adapted on the curved surface of the doctoring means 3 facing the web 2.

In FIG. 5 is shown an arrangement wherein there is placed upstream in front of the application zone of the applicator nozzle 1 a doctor bar 3 so that the bar makes a contact with the moving web 2 thus preventing the boundary air layer traveling on the moving web from reaching the application zone.

In FIG. 6 is shown an embodiment wherein there is placed downstream after the applicator nozzle 1 in the travel direction of the moving web 2 a gas-injection nozzle 5 extending over the cross-machine width of the web and adapted to direct a gas jet toward the coating mix curtain falling from the applicator nozzle. In the context of the present invention, the term gas is used when reference is made to any substance occurring in a gas phase including air, other gases and steam. When the combined momentum of the gas jet directed from the gasinjection nozzle 5 and the falling curtain of coating mix is sufficiently large as compared with the momentum of the boundary air layer traveling on the surface of the moving web 2, the coating mix curtain can unobstructedly adhere to the surface of the web 2. The streams flowing out from the applicator nozzle 1 and the gas-injection nozzle 5 are aligned to meet with each other before the coating mix curtain impinges on the web 2. By altering

From San Control of the Control of t

20

25

the operating pressure of the gas-injection nozzle 5, the adherence of the coating mix layer to the surface of the web 2 can be controlled.

In FIG. 7 is shown an embodiment different from that of FIG. 6 by having a doctoring means 3 added upstream in front of the applicator nozzle 1 in the travel direction of the web 2 so as to remove the boundary air layer from the surface of the moving web 2. Herein, the doctoring means 3 serves to remove a portion of the boundary air layer, while the gas-injection nozzle 5 assures unobstructed adherence of the coating mix curtain to the surface of the web 2.

In addition to those described above, the invention may have alternative embodiments.

A rotary or stationary small roll can be used as the doctoring means 3. Also different modifications of the above-described exemplifying embodiments may be contemplated. For instance, the doctoring means 3 used in the embodiment of FIG. 7 can be complemented when necessary with the suction nozzles 4 used in the embodiments of FIGS. 3 and 4 thus improving the efficiency of boundary air removal from the surface of the web 2.

- The state of the s
- Curtain coater for coating a moving web (2) of paper or board, the curtain coater comprising an applicator 5 nozzle (1) located above the web (2) to be coated so as to apply the coating mix therefrom to the surface of the web (2) in the form of a continuous curtain extending uniformly over the cross-machine width of the web (2), and doctoring means (3) serving to remove the boundary air layer traveling on the surface of the web (2) by 10 being located upstream in the travel direction of the web (2) in front of the impingement point of the coating mix curtain on the surface of the web (2) and further being located on the same side of the web (2) as the applicator 15 nozzle (1) c h a r a c t e r i z e d in that the surface of the doctoring means (3) facing the web is outward curved in order to support the web (2) at the doctoring point.
- 20 2. Curtain coater according to claim 1, c h a r a c t e r i z e d by a gas-injection nozzle (5) located downstream in the travel direction of the web (2) after the applicator nozzle (1) so as to extend over the cross-machine width of the web (2) and adapted to blow gas via said gas-injection nozzle toward the coating mix curtain being applied from the applicator nozzle (1).
  - 3. Curtain coater according to claim 1 or 2, c h a r a c t e r i z e d by a suction nozzle (4) extending over the cross-machine width of the web (2) and adapted to said doctoring means (3) so as to remove by suction the boundary air layer traveling on the surface of the web

10

30

(2).

- 4. Curtain coater according to claim 3, c h a r a c t e r i z e d in that the inlet opening (7) of the suction nozzle (4) is adapted to rear wall of the doctoring means (3).
- 5. Curtain coater according to claim 3 or 4, c h a r a c t e r i z e d in that the inlet opening (7) of the suction nozzle (4) is adapted to the surface of the doctoring means (3) facing the web (2).
- 6. Curtain coater according to any one of foregoing claims, c h a r a c t e r i z e d in that the surface
  15 of the doctoring means (3) facing the web (2) has a curved shape.
- Curtain coater according to claim 6, c h a r a c t e r i z e d in that the distance of the web (2) from the curved surface of the doctoring means (3) is in the range of 0-500 μm.
- Curtain coater according to any one of foregoing claims, characterized in that said
   doctoring means (3) is a doctor bar.
  - 9. Curtain coater according to any one of foregoing claims, c h a r a c t e r i z e d in that the distance along the surface of the web (2) from the doctoring point of said doctoring means (3) to the application point under said applicator nozzle (1) is less than 50 mm.

5

10

15

- 10. Curtain-coating method for coating a moving web (2) of paper or board, in which method
  - the web (2) to be coated is passed to a coater station,
  - using an applicator nozzle (1) located above the web (2), the coating mix is therefrom applied to the surface of the web (2) in the form of a continuous curtain extending uniformly over the cross-machine width of the web (2), and
  - the boundary air layer traveling along with the web is removed from the surface of the web (2) facing said applicator nozzle (1) with the help of a doctoring means (3) located upstream in the travel direction of the web (2) in front of the applicator nozzle (1),
- 20 characterized in that outward curved doctoring means (3) is used in order to support the web (2) at the doctoring point.
- 11. Curtain-coating method according to claim 10,
  25 characterized in that gas is blown toward
  the coating mix curtain being applied from the applicator
  nozzle (1) from a gas-injection nozzle (5) that is located downstream in the travel direction of the web (2)
  after the applicator nozzle (1) and is adapted to extend
  over the cross-machine width of the web (2).
  - 12. Curtain-coating method according to claim 10 or 11,

c h a r a c t e r i z e d in that the boundary air layer traveling on the surface of the web (2) is removed by suction applied by a suction nozzle (4) adapted to said doctoring means (3).

5

#### (19) World Intellectual Property Organization International Bureau



### 

#### (43) International Publication Date 8 March 2001 (08.03.2001)

**PCT** 

## (10) International Publication Number WO 01/16427 A1

(51) International Patent Classification<sup>7</sup>: B05C 5/02

D21H 23/48,

(21) International Application Number:

PCT/FI00/00746

(22) International Filing Date:

1 September 2000 (01.09.2000)

(25) Filing Language:

Finnish

(26) Publication Language:

English

(30) Priority Data:

19991863

1 September 1999 (01.09.1999) F

(71) Applicant (for all designated States except US): VALMET CORPORATION [FI/FI]; Fabianinkatu 9 A, FIN-00130 Helsinki (FI).

(72) Inventors; and

- (75) Inventors/Applicants (for US only): KIIHA, Timo [FI/US]; 25 Bluemound Ct., Apt. 6, Appleton, WI 54914 (US), KOSKINEN, Jukka [FI/FI]; Vehkatie 89, FIN-04400 Järvenpää (FI).
- (74) Agent: SEPPO LAINE OY; Itämerenkatu 3 B, FIN-00180 Helsinki (FI).

(81) Designated States (national): AE, AG, AL, AM, AT, AT (utility model), AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, CZ (utility model), DE, DE (utility model), DK, DK (utility model), DM, DZ, EE, EE (utility model), ES, FI, FI (utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

#### Published:

With international search report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: CURTAIN COATER AND METHOD FOR CURTAIN COATING



(57) Abstract: The present invention relates to a curtain coater and a curtain-coating method for coating a moving web (2) of paper or board. The curtain coater comprises an applicator nozzle (1) located above the web (2) to be coated so as to apply the coating mix therefrom to the surface of the web (2) in the form of a continuous curtain extending uniformly over the cross-machine width of the web (2). The boundary air layer traveling on the surface of the web (2) is removed by a doctoring means (3) which is located upstream in the travel direction of the web (2) in front of the impingement point of the coating mix curtain on the surface of the web (2) and is further located on the same side of the web (2) as the applicator nozzle (1).

1/16427 A1






Fig. 1




Fig. 2




Fig. 3




Fig. 4

PCT/F100/00746




Fig. 5




Fig. 6




Fig. 7

# COMBINED DECLARATION FOR PATENT APPLICATION AND POWER OF ATTORNEY Includes Reference to PCT International Applications

Attorney's Docket No.

As a below nan	ned inventor, I hereby declar	are that:			
My residence, post offic	e address and citizenship a	re as stated below next	t to my name.		
	nal, first and sole inventor (s are listed below) of the su	ibject matter which is	claimed and for which		
me invention entitled.	Curtain coater a	nd method for cu	urtain coating		
he specification of which	ch (check only one item bel	low)			
is attached h	ereto				
was filed as	United States application				
Serial No.					
and was amend					
			(if applicable).		
<del></del>	PCT international applicati	ion			
Number	PCT/F100/00746	<u> </u>			
on	September 1, 2000				
and was amend	ed under PCT Article 19				
on			(if applicable).		
claims, as amended by a lacknowledge the duty of the 37, Code of Feder lacknowledge the duty of the state of America listed certificate or any PCT	ave reviewed and understated any amendment referred to to disclose information white all Regulations, §1.56(a).  Priority benefits under Title or of any PCT international delow and have also international application (state the same subject matter has	above.  ich is material to the particle 35, United States Cool application(s) design dentified below any solution of the state of the s	de, §119 of any foreign atting at least one coun foreign application(s) t one country other the	cation in accordance application(s) try other than for patent or than the United	dance wi for pate the Unite inventor
	PCT APPLICATIONS A	T T	1		
Country (if PCT, indicat		Application Number	Date of Filing (day, month, year)	Priority ( Under 35 U	
Finland		19991863	1 September 1999	X YES	[]N
PCT		PCT/FI00/00746	1 September 2000	[X] YES	[]N
				[]YES	[] N
		ļ		[]YES	[]N
				[] YES	[] No

## COMBINED DECLARATION FOR PATENT APPLICATION AND POWER OF ATTORNEY (Continued)

Attorney's Docket No.

Includes Reference to PCT International Applications

Send correspondence to:

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) or PCT international application(s) designating the United States of America that is/are listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in that/those prior application(s) in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application(s) and the national or PCT international filing date of this application:

PRIOR U.S. APPLICATIONS OR PCT INTERNATIONAL APPLICATIONS DESIGNATING THE U.S. FOR BENEFIT UNDER 35 U.S.C. 120:

	U.S. APPLICATIONS	STATUS (check one)			
U.S. APPLICA	ATION NUMBER	U.S. FILING DATE	PATENTED	PENDING	ABANDONED
				· · · · · · · · · · · · · · · · · · ·	
) 					
	LICATIONS DESIGNATI	NG THE U.S.			
PCT APPLICATION NO.	PCT FILING DATE	U.S. SERIAL NUMBERS ASSIGNED (if any)			
PCT/F100/00746	1 September 2000			x	
instruction of the control of the co					
12					

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (List name and registration number)

MYRON COHEN, Reg. No. 17,358; THOMAS C. PONTANI, Reg. No. 29,763; LANCE J. LIEBERMAN, Reg. No. 28,437; MARTIN B. PAVANE, Reg. No. 28,337; MICHAEL C. STUART, Reg. No. 35,698; KLAUS P. STOFFEL, Reg. No. 31,668; EDWARD M. WEISZ, Reg. No. 37,257; CHI K. ENG, Reg. No. 38,870; JULIA S. KIM, Reg. No. 36,567; VINCENT M. FAZZARI, Reg. No. 26,879; ALFRED W. FROEBRICH, Reg. No. 38,887. 37,897; ANDRES N. MADRID, Reg. No. 40,710

	551 Fifth A			(name and telephone number)  Michael C. Stuart (212) 687-2770
	FULL NAME OF INVENTOR	FAMILY NAME Kiiha	FIRST GIVEN NAME Timo	SECOND GIVEN NAME
2	RESIDENCE & CITIZENSHIP	CITY Menasha	STATE OR FOREIGN COUNTRY WI	COUNTRY OF CITIZENSHIP Finland
1	POST OFFICE ADDRESS	POST OFFICE ADDRESS 1320 Geneva Rd, Apt 7	<b>city</b> Menasha	STATE & ZIP CODE/COUNTRY WI 54952, U.S.A.
73	FULL NAME OF INVENTOR	FAMILY NAME Koskinen	FIRST GIVEN NAME Jukka	SECOND GIVEN NAME
2	RESIDENCE & CITIZENSHIP	<b>спү</b> Järve <u>npää</u>	STATE OR FOREIGN COUNTRY Finland	COUNTRY OF CITIZENSHIP Finland
2	POST OFFICE ADDRESS	POST OFFICE ADDRESS Vehkatie 89	cīty FIN-04400 Järvenpää	STATE & ZIP CODE/COUNTRY Finland

Direct Telephone calls to:

Con	ibined Declarati	ion for Patent Application and Poto PCT International Applications)	ower of Attorney (Continued)	Attorney's Docket No.
(ALC	FULL NAME OF INVENTOR	FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME
2	RESIDENCE & CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
3	POST OFFICE ADDRESS	POST OFFICE ADDRESS	CITY	STATE & ZIP CODE/COUNTRY
	FULL NAME OF INVENTOR	FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME
2	RESIDENCE & CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
4	POST OFFICE ADDRESS	POST OFFICE ADDRESS	CITY	STATE & ZIP CODE/COUNTRY
2 25	FULL NAME OF INVENTOR	FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME
2	RESIDENCE & CITIZENSHIP	СІТУ	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
5	POST OFFICE ADDRESS	POST OFFICE ADDRESS	СІТУ	STATE & ZIP CODE/COUNTRY
esse marage	FULL NAME OF INVENTOR	FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME
2	RESIDENCE & CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
6	POST OFFICE ADDRESS	POST OFFICE ADDRESS	CITY	STATE & ZIP CODE/COUNTRY
10 10 10 10 10 10 10 10 10 10 10 10 10 1	FULL NAME OF INVENTOR	FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME
2	RESIDENCE & CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
7	POST OFFICE ADDRESS	POST OFFICE ADDRESS	CITY	STATE & ZIP CODE/COUNTRY
	FULL NAME OF INVENTOR	FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME
2 0	RESIDENCE & CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
8	POST OFFICE ADDRESS	POST OFFICE ADDRESS	CITY	STATE & ZIP CODE/COUNTRY
	FULL NAME OF INVENTOR	FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME
2 0	RESIDENCE & CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
9	POST OFFICE ADDRESS	POST OFFICE ADDRESS	CITY	STATE & ZIP CODE/COUNTRY

Cor (Inc	nbined Declarat	ion for Patent Applic to PCT Internationa	ation and Po	wer of Attorney (Continued) s)	Attorney's Doc	ket No.	
	FULL NAME OF INVENTOR	FAMILY NAME		FIRST GIVEN NAME	SECOND GIVEN NAME	}	
2	RESIDENCE & CITIZENSHIP	CITY		STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZEN	ISHIP	
0	POST OFFICE ADDRESS	POST OFFICE ADDRESS		CITY	STATE & ZIP CODE/CO	OUNTRY	
	FULL NAME OF INVENTOR	FAMILY NAME		FIRST GIVEN NAME	SECOND GIVEN NAME	3	
2	RESIDENCE & CITIZENSHIP	CITY		STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZEN	NSHIP	
1	POST OFFICE ADDRESS	POST OFFICE ADDRES	S	CITY	STATE & ZIP CODE/CO	OUNTRY	
	FULL NAME OF INVENTOR	FAMILY NAME		FIRST GIVEN NAME	SECOND GIVEN NAMI	E	
2	RESIDENCE & CITIZENSHIP	CITY		STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZE	NSHIP	
2	POST OFFICE ADDRESS	POST OFFICE ADDRESS		CITY	STATE & ZIP CODE/Co	STATE & ZIP CODE/COUNTRY	
15 17 17 17 17 17 17 17 17 17 17 17 17 17	information that willful §1001 of T	n and belief are believe false statements and t	ed to be true; the like so mad tates Code and	of my own knowledge are true and further that these statement de are punishable by fine or im d that such willful false statem.	were made with the knowler erisonment, or both, under	edge	
SIG	NAPURE OF INVE	ORE OF INVENTOR 201 SIG		of inventor 202	SIGNATURE OF INVENTOR 2	IGNATURE OF INVENTOR 203	
DA	February	Edoman 20,2002		ary 25, 2002	DATE		
SIC	NATURE OF INVE			OF INVENTOR 205	SIGNATURE OF INVENTOR 2	3NATURE OF INVENTOR 206	
DA	ATE	TE.			DATE		
DATE			SIGNATURE	OF INVENTOR 208	SIGNATURE OF INVENTOR 209		
			DATE D.		DATE		
			SIGNATURE	OF INVENTOR 211	SIGNATURE OF INVENTOR 2	212	
	ATE DATE				ATE		